	4 3 2 1	
	NOTES CONTINUED: REV. DATE DCN # DRAWING TREE #	
	Scribe, ENGRAVE, OR MECHANICALLY STAMP (NO INKS OR DYES) DRAWING PART NUMBER, REVISION (AND	
	VARIANT OR "TYPE" IF APPLICABLE) ON NOTED SURFACE	
	DIGIT SERIAL NUMBER SERIAL NUMBERS START AT 101 FOR THE FIRST ARTICLE AND PROCEED CONSECUTIVELY.	
	USE MINIMUM 0.12" HIGH CHARACTERS, UNLESS THE SIZE OF THE PART DICTATES SMALLER CHARACTERS.	
D	A VIBRATORY TOOL MAY BE USED. EXAMPLE: DXXXXXX-VY, TYPE-XX, S/N XXX	D
	6. APPROXIMATE WEIGHT = 0.034g 7. MACHINE ALL SURFACES TO REMOVE OXIDES AND MILL FINISH,	
	USE OF ABRASIVE REMOVAL TECHNIQUES IS NOT ALLOWED.	
	8. ALL PARTS SHALL BE MANUFACTURED IN ACCORDANCE WITH LIGO SPECIFICATION E0900364.	
	ISOMETRIC VIEW	
С		С
	$-\phi.079$	
->		ŧ
В	-( $-+ )$ $$ $0.040$	В
	$\psi$ .040	
	90.0	
А		А
	NOTES AND TOLERANCES: (UNLESS OTHERWISE SPECIFIED)	
	2. REMOVE ALL SHARP EDGES, R.02 MIN.	
	4. ALL MACHINING FLUIDS MUST BE FULLY SYNTHETIC, FULLY WATER SOLUBLE AND FOR EQ SULF AND CHI OPINIE AND CHI OP	
	ANGULAR ± 0.5° 6061-T6 AI 32 µinch HSTS TEST MASS APPROVAL SCALE: 16:1 PROJECTION: + SHEET 1 OF 1	
	4 3 2 1	
	D0902431_AdvLIGO_SUS_HSTS_Magnet Standoff, Test Mass, PART PDM REV: V1, DRAWING PDM REV: V1	