



**HAM4 Beam Splitter for the H1 Squeezer**

APPROVALS	DATE	RE V	DCN NO.	BY	CHECK	DCC	DATE
AUTHOR: L. BARSOTTI	8-26-10						
CHECKED:							
APPROVED: D.SIGG							
DCC RELEASE							

**1 Description**

2" Ø Flat/Flat beam splitters @ 1064nm

**2 Material**

Corning HPFS 7980 (high purity fused silica, UV grade)  
Grade 0A (Low inclusion class: <0.3 mm<sup>2</sup> cross section, 0.1 mm max. size;  
Homogeneity < 1ppm)

**3 Dimensions**

2"Ø +.000/-.005" X .375" ± .020" tk., Plano / Plano

**4 Wedge**

30 arc minutes ± 5 arc minutes

**5 Surface Roughness**

**Side 1**

Super polish  
Surface Roughness: <1Å RMS in CA  
Surface Quality: 10-5

**Side 2**

Commercial Polish  
Surface Roughness: <5Å RMS in CA  
Surface Quality: 20-10

**6 Surface Figure**

**Side 1**

Flat < λ/10 at 632.8 over central 80%

**Side 2**

Flat < λ/10 at 632.8 over central 80%



## SPECIFICATION

**HAM4 Beam Splitter for the H1 Squeezer****7 Coating****BEAM SPLITTER**

Wavelength: 1064nm

Angle of incidence:  $45^\circ \pm 5\%$ **Side 1**R =  $99\% \pm 0.2\%$  for **p**-polarization**Side 2**AR coating, R < 0.1% (best effort) for **p**-polarization

Serial numbers and registration marks shall be scribed or etched on the barrel of the optic for in-vacuum use

**Coating vendor to provide:**

1. Two spectrophotometer graphs of the reflectance and transmittance of the HR coatings; one covering the spectrum from 530nm to 1200nm; the other, with increased sensitivity, showing wavelengths from 900nm to 1100nm
2. Spectrophotometer graphs of the reflectance of the AR coating taken as cited above.