

REV.	DATE	DCN #	DRAWING TREE #

NOTES CONTINUED:

- SCRIBE, ENGRAVE, OR MECHANICALLY STAMP (NO INKS OR DYES) DRAWING PART NUMBER AND REVISION ON NOTED SURFACE FOLLOWED ON THE NEXT LINE BY A THREE DIGIT SERIAL NUMBER. SERIAL NUMBERS START AT 001 FOR THE FIRST ANGLE AND PROCEED CONSECUTIVELY. USE 07 HIGH CHARACTERS. A EXAMPLE: DXXXXXX.VV.5N.001
- APPROXIMATE WEIGHT - X.XXXX LB.
- MACHINE ALL SURFACES TO REMOVE OXIDES AND MILL FINISH. USE OF ABRASIVE REMOVAL TECHNIQUES IS NOT ALLOWED. REFER TO LIGO E0900364
- ALL PARTS SHALL BE MANUFACTURED IN ACCORDANCE WITH LIGO SPECIFICATION E0900364.

- ALL MATERIAL IS TO BE VIRGIN MATERIAL (i.e. NO WELD REPAIRS, PLUGS OR RECYCLED MATERIAL). NO REPAIRS SHALL BE MADE UNLESS APPROVED IN ADVANCE. AND IN WRITING, BY LIGO LABORATORY. REFER TO LIGO E0900364.
- SURFACE FINISH TO BE AS PROCESSED FROM MILL/SUPPLIER, FREE FROM SCRATCHES OR GOUGES.
- ALL PARTS WILL BE PORCELAIN COATED PER LIGO SPECIFICATION E0900364. AFTER FABRICATION, THE PORCELAIN COATING SHALL BE MASKED PRIOR TO PORCELAIN COATING. APPROXIMATELY 1/16" HOLE DIAMETER CENTERED ON BOTH SIDES OF THE HOLE.
- ALL PARTS SHALL BE MANUFACTURED IN ACCORDANCE WITH LIGO SPECIFICATION E0900364.



NOTES 9, 10, 13 and 14 DO NOT APPLY TO THIS PART

V25AM-33-A CABLE ASSEMBLY CIRCUIT SUMMARY

VμD25 M/1S-33-4_μD9 F/5S:A

FROM				
CONNECTOR J1 - 25 PIN MALE MICRO_D CONNECTOR				
PIN	WIRE NAME	COLOR	LENGTH	TWISTED PAIR
E1	(CONNECTOR SHELL)			
E1	(CABLE 1) WIRE 1	White	33 in.	(CABLE 1) SHIELD SINGLE WIRE
E14	(CABLE 1) WIRE 14	White	33 in.	TP-1A
E2	(CABLE 1) WIRE 2	White	33 in.	TP-1A
E15	(CABLE 1) WIRE 15	White	33 in.	TP-2A
E3	(CABLE 1) WIRE 3	White	33 in.	TP-2A
E16	(CABLE 1) WIRE 16	White	33 in.	TP-3A
E4	(CABLE 1) WIRE 4	White	33 in.	TP-3A
E17	(CABLE 2) WIRE 17	White	33 in.	(CABLE 2) SHIELD TP-1B
E5	(CABLE 2) WIRE 5	White	33 in.	TP-1B
E18	(CABLE 2) WIRE 18	White	33 in.	TP-2B
E6	(CABLE 2) WIRE 6	White	33 in.	TP-2B
E19	(CABLE 2) WIRE 19	White	33 in.	TP-3B
E7	(CABLE 2) WIRE 7	White	33 in.	TP-3B
E1	(CABLE 3) WIRE 20	White	33 in.	(CABLE 3) SHIELD TP-1C
E20	(CABLE 3) WIRE 20	White	33 in.	TP-1C
E8	(CABLE 3) WIRE 8	White	33 in.	TP-2C
E21	(CABLE 3) WIRE 21	White	33 in.	TP-2C
E9	(CABLE 3) WIRE 9	White	33 in.	TP-3C
E22	(CABLE 3) WIRE 22	White	33 in.	TP-3C
E10	(CABLE 3) WIRE 10	White	33 in.	TP-3C
E1	(CABLE 4) WIRE 23	White	33 in.	(CABLE 4) SHIELD TP-1D
E23	(CABLE 4) WIRE 23	White	33 in.	TP-1D
E11	(CABLE 4) WIRE 11	White	33 in.	TP-2D
E24	(CABLE 4) WIRE 24	White	33 in.	TP-2D
E12	(CABLE 4) WIRE 12	White	33 in.	TP-2D
E25	(CABLE 4) WIRE 25	White	33 in.	TP-3D
E13	(CABLE 4) WIRE 13	White	33 in.	TP-3D

TEST LIST		TEST LIST		TEST LIST		TEST LIST	
FROM	TO	FROM	TO	FROM	TO	FROM	TO
J1	J2	J1	J3	J1	J4	J1	J5
PIN	PIN	PIN	PIN	PIN	PIN	PIN	PIN
J1 - 1, SHELL	J2 - 5, SHELL	J1 - 1, SHELL	J3 - 5, SHELL	J1 - 1, SHELL	J4 - 5, SHELL	J1 - 1, SHELL	J5 - 5, SHELL
J1 - 2	J2 - 6	J1 - 5	J3 - 6	J1 - 8	J4 - 6	J1 - 11	J5 - 6
J1 - 15	J2 - 2	J1 - 18	J3 - 2	J1 - 21	J4 - 2	J1 - 24	J5 - 2
J1 - 3	J2 - 7	J1 - 6	J3 - 7	J1 - 9	J4 - 7	J1 - 12	J5 - 7
J1 - 16	J2 - 4	J1 - 19	J3 - 4	J1 - 22	J4 - 4	J1 - 25	J5 - 4
J1 - 4	J2 - 9	J1 - 7	J3 - 9	J1 - 10	J4 - 9	J1 - 13	J5 - 9



V25AM-33-A CABLE ASSEMBLY CIRCUIT SUMMARY

TO

CONNECTOR J2 - 9 PIN FEMALE MICRO_D CONNECTOR (PEEK)		
PIN	WIRE NAME	SIGNAL
A5	(CONNECTOR SHELL)	SHIELD
A5	(CABLE 1) SHIELD	SHIELD
A1	(CABLE 1) WIRE 14	PD1-K
A2	(CABLE 1) WIRE 2	PD1-A
A7	(CABLE 1) WIRE 3	LED1-K
A4	(CABLE 1) WIRE 16	COIL1-FN
A9	(CABLE 1) WIRE 4	COIL1-ST

TO

CONNECTOR J3 - 9 PIN FEMALE MICRO_D CONNECTOR (PEEK)		
PIN	WIRE NAME	SIGNAL
B5	(CONNECTOR SHELL)	SHIELD
B5	(CABLE 2) SHIELD	SHIELD
B1	(CABLE 2) WIRE 17	PD2-K
B6	(CABLE 2) WIRE 5	PD2-A
B2	(CABLE 2) WIRE 18	LED2-A
B7	(CABLE 2) WIRE 6	LED2-K
B4	(CABLE 2) WIRE 19	COIL2-FN
B9	(CABLE 2) WIRE 7	COIL2-ST

TO

CONNECTOR J4 - 9 PIN FEMALE MICRO_D CONNECTOR (PEEK)		
PIN	WIRE NAME	SIGNAL
C5	(CONNECTOR SHELL)	SHIELD
C5	(CABLE 3) SHIELD	SHIELD
C1	(CABLE 3) WIRE 20	PD3-K
C6	(CABLE 3) WIRE 8	PD3-A
C2	(CABLE 3) WIRE 21	LED3-A
C7	(CABLE 3) WIRE 9	LED3-K
C4	(CABLE 3) WIRE 22	COIL3-FN
C9	(CABLE 3) WIRE 10	COIL3-ST

TO

CONNECTOR J5 - 9 PIN FEMALE MICRO_D CONNECTOR (PEEK)		
PIN	WIRE NAME	SIGNAL
D5	(CONNECTOR SHELL)	SHIELD
D5	(CABLE 4) SHIELD	SHIELD
D5	(CABLE 4) WIRE 1	SHIELD
D1	(CABLE 4) WIRE 23	PD4-K
D6	(CABLE 4) WIRE 11	PD4-A
D2	(CABLE 4) WIRE 24	LED4-A
D7	(CABLE 4) WIRE 12	LED2-K
D4	(CABLE 4) WIRE 25	COIL4-FN
D9	(CABLE 4) WIRE 13	COIL4-ST



BILL OF MATERIALS

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	LENGTH
1	GLENAIR #DCDM25P-S-MC225-240 TICOR # 040-1243-0025	MicroD25 MALE CONNECTOR (J1) FOR UHV (STAINLESS STEEL OVER LCP)	1	1
2	TICOR # 040-1243-0025	MicroD25 CONNECTOR BACKSHELL FOR UHV (STAINLESS STEEL) WITH QUAD ø0.100" I.D. PORTS	1	1
3	TICOR # TS0904 WITH 60in. FLYING LEADS WITH BACKSHELL	MicroD9 FEMALE CONNECTOR (J2,J3,J4,J5) FOR UHV (PEEK)	4	4
4	C1	MicroD9 CONNECTOR BACKSHELL FOR UHV (STAINLESS STEEL) WITH ø0.185" I.D. PORT WITH ① COPPER BRAID (SHIELD) AND ② PEEK OVERBRAID.	4	4
5		7 COND. (3 TWISTED PAIR) CABLE WITH ③ COPPER BRAID (SHIELD) AND ④ PEEK OVERBRAID.	4	33in.*
6	CONTINENTAL PART # 24x3x40BC	CONTINENTAL CORDAGE COPPER BRAID	4	
7	PART # 6759	PEEK BRAID PART # 6759 MANUFACTURED WITH ZEUS 0.016" BLACK PEEK DRAWN MONOFILAMENT	4	
8	GLENAIR # 600-052 or BAND-IT # A10086	GLENAIR # 600-052 STANDARD BRAID CLAMP or BAND-IT PART # A10086 (0.240" WIDE) ("BAG OF 100" # A10089)	8	

* NOTE: THE OVERALL LENGTH IS MEASURED FROM PIN TIP (25 PIN) TO PIN TIP (9 PIN) OF THE CABLE. USE WHATEVER LENGTH IS NECESSARY FOR THE INTERNAL WIRING OF THE CONNECTORS AND STRIP LENGTH TO ACHIEVE THE CORRECT OVERALL LENGTH.

NOTES: (UNLESS OTHERWISE SPECIFIED)

- MATERIAL:
 - 25 PIN CONNECTOR SHELL - J1 (E) STAINLESS STEEL OVER LCP - (LIQUID CRYSTAL POLYMER per MIL-M-24519).
 - 9 PIN CONNECTOR SHELL - J2 (A), J3 (B), J4 (C), J5 (D) - PEEK - VICTREX 450GL30.
 - CONTACTS - BERYLLIUM COPPER ALLOY C17300, 0.00050 MIN. GOLD OVER NICKEL.
 - HARDWARE - STAINLESS STEEL, PASSIVATED.
 - PEEK BRAID - PEEK VICTREX GRADE TDS-450CA30 CARBON LOADED - SUPPLIED BY LIGO.
- CABLE 7 COND. 28 AWG, (40 STRD 44 AWG) WITH PFA INSULATION. 3 TWISTED PAIRS (4 TO 5 TWISTS PER INCH). OVERALL 40AWG COPPER BRAID 90% COVERAGE. OVERALL PEEK BRAID MIN. 50% COVERAGE. OVERALL CABLE O.D. WILL BE APPROX. 0.240 IN.
- CONNECTORS WILL BE SUPPLIED WITH HARDWARE. SCREWS SHOULD BE THE PROPER LENGTH FOR MATING.



VμD25 M/1S-33-4_μD9 F/5S:A

STANDARD USE FOR THIS CABLE

SUBSYSTEM	STANDARD USE
SUS	QUAD SUSPENSIONS PUM

DIMENSIONS ARE IN		NOTES AND TOLERANCES: (UNLESS OTHERWISE SPECIFIED)		LIGO CALIFORNIA INSTITUTE OF TECHNOLOGY MASSACHUSETTS INSTITUTE OF TECHNOLOGY		PART NAME	
XXX ±	XXX ±	1. INTERPRET DRAWING PER ASME Y14.5-1994.	2. REMOVE ALL SHARP EDGES. 0.05-0.015 FOR MACHINED PARTS. ROUND ALL EDGES APPROXIMATELY R.02 FOR SHEET METAL PARTS.	SYSTEM	SUS	DESIGNER	J. HEFFNER
ANGULAR ±	ANGULAR ±	3. DO NOT SCALE FROM DRAWING.	4. ALL MACHINING FLUIDS MUST BE FULLY SYNTHETIC, FULLY WATER SOLUBLE AND FREE OF SULFUR, SILICONE, AND CHLORINE.	CHECKER	E. BROWN	DATE	08/13/2012
				APPROVAL		DWG. NO.	D1000564
						REV.	v5
						SCALE	2:1
						PROJECTION	
						SHEET	1 OF 1