


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	LENGTH
1		DB25 MALE CONNECTOR (J1) FOR UHV (GOLD METALIZED PEEK)	1	
2	(TS0149-25CG20BS1-325F) OR EQUIVALENT	DB25 CONNECTOR BACKSHELL (WITH EARS) (LARGE PORT) FOR UHV (STAINLESS)	1	
3	TICOR # (TS0148-25CG20BS1-325F) OR EQUIVALENT	DB25 FEMALE CONNECTOR (J2) FOR UHV (GOLD METALIZED PEEK)	1	
4		DB25 CONNECTOR BACKSHELL (WITH EARS) (LARGE PORT) FOR UHV (STAINLESS)	1	
5	COONER WIRE # CZ2205 + 8 + 9	16 COND. 22Ga. (8 TWISTED PAIR) CABLE WITH 6 COPPER BRAID (SHIELD) AND 7 PEEK OVERBRAID	1	143in *
6	CONTINENTAL PART #24x3x40BC	COPPER BRAID - CONTINENTAL CORDAGE PART #24x3x40BC	1	143in *
Ī	#6759	PEEK BRAID - PART #6759 MANUFACTURED WITH ZEUS 0.016" BLACK PEEK DRAWN MONOFILAMENT	1	143in *
8	GLENAIR # 600-052 or BAND-IT # A10086	GLENAIR # 600-052 STANDARD BRAID CLAMP or BAND-IT PART # A10086 (0.240" WIDE) ("BAG OF 100" # A10089)	2	
9	HELICOIL #1185-04EN336	#4-40 Nitronic 60® HELICOIL 0.336" LENGTH	2	

D

С



DCN #	DRAWING TREE #

		Ø 0.375in[9.53mm]
		0.050in[1.27mm]
		1.673in[42.49mm]
Z		0.375in[9.53mm]
	I I	7

	-		-		
	COND WIRE ID	TWISTED PAIR	LENGTH	FROM	то
	16 COND. CABLE	(8 TOTAL)	143 in.	Conn. J1	Conn. J2
	SHIELD		143 in	PIN 1, SHELL	PIN 1, SHELL
	W13	TP-1	143 in	PIN 13	PIN 13
	W25		143 in	PIN 25	PIN 25
	W12	TP-2	143 in	PIN 12	PIN 12
	W24		143 in	PIN 24	PIN 24
	W11	TP-3	143 in	PIN 11	PIN 11
	W23		143 in	PIN 23	PIN 23
	W10	TP-4	143 in	PIN 10	PIN 10
	W22		143 in	PIN 22	PIN 22
	W9	TP-5	143 in	PIN 9	PIN 9
	W21		143 in	PIN 21	PIN 21
	W8	TP-6	143 in	PIN 8	PIN 8
	W20		143 in	PIN 20	PIN 20
	W7	TP-7	143 in	PIN 7	PIN 7
	W19		143 in	PIN 19	PIN 19
	W6		143 in	PIN 6	PIN 6
	W18	TP-8	143 in	PIN 18	PIN 18
_	>				

В

	STANDARD USE
IN-VAC	PICOMOTORS TOP TO TABLE

REV. **V**5 Sheet 1 of 1 (-)