NOTES CONTINUED:	
 MACHINE ALL SURFACES TO REMOVE OXIDES AND MILL FINISH, USE OF ABRASIVE REMOVAL TECHNIQUES IS NOT ALLOWED. 8. ALL PARTS SHALL BE MANUFACTURED IN ACCORDANCE WITH LIGO SPECIFICATION E0900364. 9. NO REPAIRS SHALL BE MADE UNLESS APPROVED IN ADVANCE, AND IN WRITING, BY LIGO LABORATORY. IN GENERAL WELD REPAIRS AND PRESS FIT INSERT REPAIRS ARE NEVER ACCEPTABLE: THE MATERIAL SHOUL DBE MADE WITH VIRGIN MATERIAL. SPECIAL CIRCUMSTANCES CAN BE REVIEWED IF / WHEN BROUGHT TO THE ATTENTION OF LIGO CONTRACTING OFFICER'S REPRESSITUTIVE (COTR) THROUGH 	
ARE NEVER ACCEPTABLE; THE MATERIAL SHOUL DBE MADE WITH VIRGIN MATERIAL. SPECIAL CIRCUMSTANCES CAN BE REVIEWED IF / WHEN BROUGHT TO THE ATTENTION OF LIGO CONTRACTING OFFICER'S REPRESENTITIVE (COTR) THROUGH	
$\sqrt{-\langle 5 \rangle}$	
	(1.00)
.27 7.44	
R.38	
	V
-01 (RIGHT HANDED) SHOWN DETAILED -02 (LEFT HANDED) BEND OPPOSITE	
IQUERANCES: 2. DO NOT SCALE FROM DRAWING.	GO CALIFORNIA INSTITUTE OF TECHNO MASSACHUSETTS INSTITUTE OF TECHNO MOVANCED LIGO



