



Surface treatment: Electropolishing and light nickel-plating  
 Trattamento superficiale: Elettropulitura enichelatura leggera

Thermal treatment: Baking at 435° for 100 hours in argon atmosphere  
 Trattamento termico: Riscaldamento a 435° per 100 ore in atmosfera di argon

length (mm)	reference width (mm)	25 full blade (mm)	25.1 3/4 blade (mm)	25.2 1/2 blade (mm)	25.3 1/4 blade (mm)
0.00	36	40.00	30.00	20.00	10.00
27.26	36.28	40.31	30-33	20.15	10.07
54.52	35.63	39.58	29.69	19.79	9.89
81.78	34.06	37.84	28.38	18.92	9.46
109.04	31.62	35.13	26.35	17.56	8.78
136.30	28.38	31.53	23.65	15.76	7.88
163.56	24.44	27.15	20.36	13.57	6.78
190.82	19.91	22.12	16.59	11.06	5.53
218.08	14.92	16.57	12.43	8.28	4.14
245.34	9.61	10.67	8.01	5.33	2.67

ref.	pieces	mat. and treatments	scale	ref.	pieces	mat. and treatments	scale
25.3	8	maraging	1/1				
25.2	8	maraging	1/1				
25.1	8	maraging	1/1				
25	32	maraging	1/1				

Dimensions	< 6	> 6-30	> 30-120	> 120-315	> 315-1000	> 1000-2000	> 2000-4000	> 4000
linear Toli.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2	± 2	± 3
angular Toli.	± 1'	± 30'	± 20'	± 10' referred to the shortest side				

		<b>LIGO PROJECT</b> designed for <b>R.De Salvo</b> draw. by <b>G. Gennaro-PROMECA</b> date <b>28-12-04</b> scale <b>1/1</b>
title <b>HAM-OPTICAL BENCH</b> <b>BLADE</b>		LIGO-D051120-02-D date:1 from 106 A 2