											T 12					1		1-01		SYSTEM										
SYSTEM, APPARATUS, OR AREA POINT DESCRIPTION	INPUTS									+-	OUTPUT		UIS .			375				FEATUR				GENERAL						
	ANALOG MEASURED CALCULATED						D	BINARY			WASHINGTON AND AND AND AND AND AND AND AND AND AN	DIGITAL			ANALOG			ALARMS			PROGRAMS						.NENAL	•		
	TEMPERA TURE PRESSURE	RH KW	AIR FLOW LEVEL	GALLONS VIBRATIONS	KWH ENTHALPY	RUN TIME EFFICIENCY	WET BULB TEMP	FILTER	SMONE FREEZE AIR FLOW	METER	OFF-ON	OFF-HI-LO	MULTI-STAGE	DAMPER POSITION VALVE POSITION	SET POINT ADJUSTMENT VANE POSITION SCP CONTROL	UL AMAI OC	LOW ANALOG HI BINARY	LOW BINARY PROOF		TIME SCHEDULING	DUTY CYCLE START/STOP OPTION	ENTHALPY OPTION SMOKE CNT	TREND ALARM INSTRUCT	MAINT WK ORD		COLOR GRAPHIC		SUPPLEMENTARY NOTES		
OUTSIDE TEMERATURE	•																													
OUTSIDE RELATIVE HUMIDITY		•																												
PREHEAT COIL, HC-14	•							D					•		•	•					•		•	0						
PREHEAT COIL, HC-15	•												•		•	•					•		•	9						
AIR FILTER AF-OI (TYP 2)	•															•								9					2 SENSORS	
AIR FILTER AF-02 (TYP 2)	•															•								9					2 SENSORS	
MIXING AIR DAMPER OI														•									•	•						
MIXING AIR DAMPER 02														•									•	9						
COOLING COIL CC-01	•													•		•							•	0						
COOLING COIL CC-02	•											Ш	П	•		•							•	9						
HUMIDIFIER HU-01		•						•			T	\prod	•		•		•				•		•	9			\Box			
HUMIDIFIER HU-02		•										П	•		•	•	0			T	•		•	•	$\top 1$	\Box				
SUPPLY FAN SF-01			•	•		•		•	•		0				•	•		•		•	•		•	•	$\top 1$		\sqcap			
SUPPLY FAN SF-02			•	•		•			•		•				•	•		•		•	•		•	D	$\top 1$	$\exists \exists$				
SUPPLY AIR TEMP (TYP 2)	•						$\top \uparrow$	$\top \!$	$\top \top$			\prod					•		\top				•		$\top 1$	\top				
SUPPLY AIR RELATIVE HUMIDITY		•						TT				\prod							\top		T		•		$\top 1$					
ROOM TEMPERATURE (TYPICAL 5 ZONES)	•										T						•		\top	11	\prod		•		$\top 1$					
SPACE AVERAGE RELATIVE HUMIDITY		•						$\top \top$				\prod					•						•		$\top 1$		\sqcap			
ZONE DUCT HEATER (VEA)	•										T				•	•					•		•	D	$\top 1$					
ZONE DUCT HEATERS (TYPICAL 5 ZONES)	•							•				П	•								•			D						
SMOKE DETECTOR (SD-01)							\sqcap	•											77			•	•	\Box	$\top 1$					
MIXING AIR TEMP	•						\sqcap	$\top \!$				П				П			\top		T				$\top 1$					
MIXING AIR RELATIVE HUMIDITY		•					П	\prod			T	П				\prod			\top						\sqcap					
AIR COMPRESSORS (TYP 2)	•															•	•		\top		•						\top			
TOILET EXHAUST FAN, EF-01						•					•	\prod				\prod		•		•	•			D	11	\sqcap			,	
AIR FLOW DIAGRAM											T					П									\sqcap	•				
HEPA FILTERS	•											\prod				•								D			11			
FLOOR PLANS	1	\top	$\neg \neg $		_	\Box	+	11	11		1	11				$\top T$	$\top \top$	$\dagger \dagger \dagger$		\top			+		$\dagger \dagger$		77	1		

SYSTEM, APPARATUS, OR AREA POINT DESCRIPTION		INPUTS											OUTPUTS						SYSTEM FEATURES											
	ANALOG MEASURED CALCULATED					BINARY				DIGITAL			ANALOG		ALARMS			PROGRAMS						GENE	RAL		8			
	TEMPERATURE PRESSURE RH	KW AIR FLOW	LEVEL VIBRATIONS	KWH	RUN TIME	WET BULB TEMP	STATUS FILTER	SMUNE FREEZE ATO CLOW	AIR FLOW METER	OFF-ON	OFF-AUTO-ON OFF-HI-LO	OPEN-CLOSE MULTI-STAGE	DAMPER POSITION	SET POINT ADJUSTMENT	SCR CONTROL	HI ANALOG LOW ANALOG	HI BINARY	LOW BINARY PROOF		TIME SCHEDULING DEMAND LIMITING	DUTY CYCLE	SIARIASION OPIION ENTHALPY OPTION	SMOKE CN/ TREND	ALARM INSTRUCT MAINT WK ORD	e meneral estado en la companya de la companya del la companya de	COLOR GRAPHIC				SUPPLEMENTARY NOTES
WATER CHILLER, CH-OI	•		•		•		•							•						•										
WATER CHILLER, CH-02	•		•	T	•		•							•		9 9				•	1	9								
CHILLED WATER PUMP, WP-01	•		•	0	•	П	•									•	П	•		•	1	9		•						·
CHILLED WATER PUMP, WP-02	•		•	0	•		•			0	П		1			9		•		•	1	•		•					1	
CHILLED WATER RETURN TEMP	•			\prod																				•						
CHILLED WATER SUPPLY TEMP	•										П													•						
CHILLED WATER BOOSTER PUMP	•						•			•												9								PUMP BY VE CONTRACTOR
CHILLED WATER FLOW DIAGRAM			\top							T	П										П					•				
FLOOR PLANS			\Box							T										T	TT		T		-!-	•	1			***************************************

NO

- 1. FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES SEE SHEETS WA-H-001 AND WA-H-002.
- 2. SMOKE DETECTORS WILL BE HARD WIRED TO THE SUPPLY FANS SF-01 & SF-02 MOTOR STARTER TO STOP FANS WHEN SMOKE DETECTED IN THE RETURN AIR STREAM. ALSO SMOKE DETECTORS WILL BE SOFTWARE CONNECTED TO DDC CONTROL PANEL AND THE FACILITY CONTROL ROOM.
- 3. CONTROL SYSTEM SHALL BE STAND ALONE TYPE AND CONNECTED TO THE MAIN CONTROL AND MONITORING SYSTEM AT THE FACILITY CONTROL ROOM IN THE CORNER STATION BUILDING.
- 4. VACUUM EQUIPMENT ROOM WILL BE PROVIDED WITH FOUR TEMPERATURE SENSORS TO CONTROL THE RESPECTIVE DUCT HEATER. SYSTEM MAY AVERAGE THE READING OF THE FOUR ROOM TEMPERATURE SENSORS OR SELECT ANY SENSOR TO CONTROL THE DUCT HEATER.

SEQUENCE OF OPERATION:

I. CHILLED WATER PLANT:

UPON A SIGNAL FROM THE CENTRAL CONTROL SYSTEM THE PACKAGED CONTROLS PROVIDED WITH THE WATER CHILLER WILL PERFORM THE FOLLOWING:

- A. THE LEAD CHILLED WATER PUMP (WP-01) WILL START TO ESTABLISH STEADY WATER FLOW THROUGH THE SYSTEM.
- B. UPON PROOF OF ESTABLISHED WATER FLOW THE LEAD CHILLER (CH-OI) WILL START TO MAINTAIN THE LEAVING CHILLED WATER TEMPERATURE SETPOINT (42°F).
- C. THE PACKAGED DDC CONTROLS ON THE WATER CHILLER WILL CYCLE THE REFRIGERATION COMPRESSORS IN SECUENCE TO MATCH THE SYSTEM THERMAL LOAD.
- D. WHEN THE THERMAL LOAD DROPS BELOW THE MINIMUM OPERATING CAPACITY OF THE WATER CHILLER, THE PACKAGED CONTROL WILL ACTIVATE THE HOT GAS BYPASS CYCLE.
- E. PACKAGED CONTROLS WILL RUN SELF DIAGNOSTICS TEST BEFORE STARTING THE REFRIGERATION COMPRESSORS TO PROVE THAT ALL OPERATING CONDITIONS ARE WITHIN THE NORMAL LIMITS.
- F. PACKAGED CONTROLS WILL CONTINUOUSLY MONITOR THE CHILLER OPERATION AND REPORT ANY OPERATIONAL OR SAFETY ALARMS TO THE OPERATOR COMPUTER IN THE FACILITY CONTROL ROOM. PACKAGED CONTROLS WILL AUTOMATICALLY STOP THE MALFUNCTIONING WATER CHILLER AND START THE STANDBY CHILLER.
- G. CENTRAL CONTROL SYSTEM WILL ALTERNATE THE LEAD AND STANDBY
 WATER CHILLERS TO MAINTAIN EQUAL OPERATING PERIODS ON BOTH WATER
 CHILLERS

II. AIR HANDLING SYSTEM:

UPON A SIGNAL FROM THE CENTRAL CONTROL SYSTEM THE LEAD SUPPLY AIR FAN (SF-01) WILL START TO ESTABLISH A STEADY AIR FLOW THROUGH THE SYSTEM, THE DDC CONTROLS WILL PERFORM THE FOLLWING:

- A. MODULATE THE CONTROLLABLE PITCH VANES ON THE SUPPLY AIR FANS TO MAINTAIN THE DESIRED CONSTANT AIR VOLUME FLOW RATE REGARDLESS OF THE SYSTEM STATIC PRESSURE.
- B. THE TEMPERATURE SENSORS LOCATED DOWN STREAM OF THE OUTSIDE AIR PREHEAT COILS WILL BE USED TO CONTROL THE CAPACITY OF THE DUCT ELECTRIC HEATERS TO MAINTAIN THE OUTSIDE AIR DRY BULB TEMPERATURE AT 50°F.
- C. THE TEMPERATURE SENSOR LOCATED DOWN STREAM OF THE COOLING COIL WILL BE USED TO MODULATE THE 3-WAY CONTROL VALVE ON THE CHILLED WATER LOOP TO MAINTAIN THE LEAVING AIR DRY BULB TEMPERATURE AT THE SET POINT (50°F).
- THE SET POINT (50°F).

 D. THE DDC CONTROLS WILL COMPARE THE SPACE ROOM TEMPERATURE SENSORS AND MODULATE THE FACE AND BYPASS DAMPER BASED ON THE MOST DEMANDING ZONE.
- E. THE ROOM TEMPERATURE SENSORS (TOTAL 4) OF VACUUM EQUIPMENT AREA SHALL BE USED TO MODULATE THE SCR CONTROLS ON THE RESPECTIVE ELECTRIC DUCT HEATER TO MAINTAIN THE ROOM TEMPERATURE SETPOINT (72°F)
- F. THE ROOM TEMPERATURE SENSORS FOR OTHER ROOMS SHALL BE USED TO SEQUENCE THE CAPACITY CONTROL STAGES OF THEIR RESPECTIVE DUCT HEATERS TO MAINTAIN THE ROOM TEMPERATURE SET POINT.
- G. WHEN THE ROOM TEMPERATURE RISES 5 DEGREES F ABOVE THE SETPOINT, THE CONTROL SYSTEM SHALL REPORT AN ALARM SIGNAL TO THE FACILITY CONTROL ROOM.
- H. THE RELATIVE HUMIDITY SENSOR LOCATED IN VACUUM EQUIPMENT ROOM SHALL BE USED TO SEQUENCE THE CAPACITY CONTROL STAGES OF THE ELECTRIC HUMIDIFIER TO MAINTAIN THE SPACE MINIMUM RELATIVE HUMIDITY SETPOINT (30 % RH).
- 1. THE SMOKE DUCT DETECTOR IN THE RETURN AIR DUCTS SHALL STOP THE SUPPLY AIR FANS WHEN SMOKE IS DETECTED IN THE RETURN AIR STREAM AND REPORT AN ALARM SIGNAL (AUDIO AND VISIUAL) AT THE FACILITY CONTROL ROOM AND LOCAL CONTROL PANEL.
 THE SPACE DIFFERENTIAL PRESSURE SENSORS SHALL BE USED TO MODULATE THE MOTORIZED CONTROL DAMPERS ON THE RETURN AIR DUCTS AND THE OUTSIDE AIR DUCTS TO MAINTAIN THE SPACE PRESSURIZATION AT THE SETPOINT.

III. EQUIPMENT START UP:

- A. ALL WATER CHILLER SHALL BE SOFT START
- B. THE SUPPLY AIR FANS SF-01 & SF-02 SHALL START AT THE MINIMUM STATIC PRESSURE AND GRADUALLY INCREASE THE SYSTEM STATIC PRESSURE TO MAINTAIN THE DESIRED AIR FLOW RATE.
- C. THE BUILDING PRESSURIZATION SENSORS FOR LYEA AND OSB (LAB AREA) SHALL MODULATE THE MOTORIZED DAMPERS LOCATED ON THE RETURN AIR & OUTSIDE AIR DAMPERS TO START AT 100% RETURN AIR AND GRADUALLY MODULATE THE DAMPERS TO MAINTAIN THE BUILDING PRESSURIZATION SETPOINT.

IV. TOILET EXHAUST FAN:

A. THE TOILET EXHAUST FAN WILL RUN CONTINUOUSLY.

LIGO-D960367-01-O

| SSUED FOR CONSTRUCTION | DRAWN | CLP | 6-24-96 | CHECKED | M & 7/3/96 | ENGINEER | A A | 7/3/96 | PROJ | MOU | 7/8/96 | MOU | 7/8/96 | MOU | 7/8/96 | MOU | 7/8/96 | MOU | M

4



*

3

100 WEST WALNUT STREET PASADENA, CALIFORNIA



LASER INTERFEROMETER
GRAVITATIONAL-WAVE OBSERVATORY
SITE NO. I - HANFORD, WASHINGTON

HVAC
MID & END STATIONS
SEQUENCES OF OPERATION &
I/O SUMMARY SHEET

NONE PP150969 8094

WA-H-231

LIGOWAF.BDR

В