HOLE	QTY	TOLERANCE	DESCRIPTION
A	8	⌖ Ø .010 Ⓜ | A | B | C	Ø DRILL AND TAP .75 MIN DP, #1/4-20 UNC-3B.
B	1	⌖ Ø .010 Ⓜ | A | B |	DRILL Ø .221 THRU, CBORE Ø .625, 1.32 DEEP

NOTES

1. Deburr and break sharp edges.







UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

TOLERANCES:
FRACTIONAL ±
ANGULAR ± .10
TWO PLACE DECIMAL ±.01
THREE PLACE DECIMAL ±.005

FINISHED SURFACE RMS 125
BREAK CORNERS IN: OUT:
REMOVE ALL BURRS

MATERIAL: 303 SS
HEAT TREAT:
FINISH:

DWG. NO.	DESCRIPTION
REFERENCE DRAWINGS	

USED ON:
NEXT ASS'Y:

REV	DESCRIPTION	DCC	SYS	DET	CDS	VE	CC	BT	CHECK	DRWN	DATE
B	modify hole pattern DCN E980015-00-H									mjs	2-17-98
A	RELEASE									mjs	1-27-98
00	PRE-RELEASE									mjs	1-23-98

ISSUE DESCRIPTION

LIGO
CALIFORNIA INSTITUTE OF TECHNOLOGY
MASSACHUSETTS INSTITUTE OF TECHNOLOGY

PEM, ELECTRO-MAGNETIC
SHAKER MASS

CAD FILE: /home/tycho/matt/releasedrawings/dcne980015/d970279b.dwg
SIZE: C
DWG. NO.: D970279-B-H
SCALE:
SHEET: 1 OF 1