



(NO BRAID)
FLEX HOSE, 12" LG, 3/4" NOM ID
WITH 1 1/2" OD C.F. NON-ROT FLG.
X 2 3/4" OD, C.F. ROTATABLE FLG.

FLEX HOSE, 12" LG, 3/4" NOM. ID
WITH 2 3/4" C.F. ROTATABLE FLG.
(2 PLACES)
3/4" ELBOW AND 2 3/4" C.F.
ROTATABLE FLG.
(2 PLACES)

- NOTES**
- 1) WASHINGTON - QUANTITY (8)
USED WITH DWG. D V049-4-109
ANNULUS TUBING & 25 ION PUMP
 - 2) NO BRAID ON FLEX HOSES
 - 3) LOUISIANA QUANTITY (4) USED
WITH DWG. D V049-4-109.
 - 4) TUBING/FLANGES/FLEXHOSES, ETC.
BY SITE CONTRACTOR.
 - 5) CLEAN PER SPEC V049-2-178.
 - 6) TUBING CLASS T3 PER SPEC.
V049-2-037.
MAT'L = 304 S/S.

PROPRIETARY AND CONFIDENTIAL
THIS DOCUMENT CONTAINS PROPRIETARY
INFORMATION BELONGING TO PROCESS
SYSTEMS INTERNATIONAL, INC. OR ITS
AFFILIATED COMPANIES AND SHALL BE
USED ONLY FOR THE PURPOSE FOR
WHICH IT WAS SUPPLIED. IT SHALL NOT
BE COPIED, REPRODUCED OR OTHERWISE
USED, NOR SHALL SUCH INFORMATION BE
FURNISHED IN WHOLE OR IN PART TO
OTHERS EXCEPT IN ACCORDANCE WITH THE
TERMS OF ANY AGREEMENT UNDER WHICH
IT WAS SUPPLIED OR WITH THE PRIOR
WRITTEN CONSENT OF PROCESS SYSTEMS
INTERNATIONAL, INC. AND SHALL BE
RETURNED UPON REQUEST.

DWG. NO.	DESCRIPTION	USED ON X	REV.	DESCRIPTION	X	X	X	X	X	X	X	X	X	X	X
	UNLESS OTHERWISE SPECIFIED														
	INCHES ARE IN INCHES														
	TOLERANCES														
	FRACTIONS: ± .01														
	DECIMALS: ± .005														
	ANGLES: ± .01														
	THREE PLACE DECIMAL: ± .005														
	FURNISHED SURFACE AND AS SHOWN														
	REMOVE ALL BURRS														
	DO NOT SCALE THIS DWG.														
	REFERENCE DRAWINGS														
	NEXT ASSY: [blacked out]														
	ISSUE DESCRIPTION														

PROCESS SYSTEMS INTERNATIONAL, INC.
30 WALTON DR. WESTBOROUGH, MASSACHUSETTS 01581 USA

25 ANNULUS TUBING ISO
44" GATE VALVE
TYPE II

CAD FILE: [blacked out]
SIZE: B
D: V049-4-166
SHEET: 1 OF 1

LIG0-D970451-02-V

JAN 02 1998

25-08-1996 - 08:40:23