

A-3-S

Product Application and Description:

A-3-S is a high performance thermally cured epoxy coating that provides extreme resistance to high temperature exposure such as close proximity to stage lighting systems. A-3-S is a flat black coating with a gloss level of less than 6 at 60°F that provides an anti-reflective, glare free back drop for stage and theater lighting applications. This product can be coated on one or both sides.

Shelf Life and Storage:

It is recommended to consume all materials within 1 year from date of purchase. Best if stored in a controlled environment (72°F and 50%RH) and out of direct sunlight.

Physical Characteristics		
Test	Typical Performance	Method
Gloss	<6	Measured at 60°F
MEK Resistance	10 double rubs	Crockmeter
Heat Resistance	1 hour exposure (maintain integrity)	Altman Stage Lamp (1000W PAR 64)
Coat Weight	2.7—3.3lbs./Ream	Gravimetric

The information contained herein is derived from data believed to be reliable and is presented to assist our customers in determining whether our products are suitable for use in their application. We request that our customers test our products before use to satisfy themselves as to suitability for use. No warranty or guarantee is expressed or implied. Protection from any law or patents is not inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental, or consequential damages. Customers desiring assistance with specification, development or performance criteria for specific product applications should contact us for further information.

16100 Imperial Parkway * Strongsville, OH 44149 * Phone: (440) 572-FOIL (3645) * Fax: (440) 378-0161 * www.allfoils.com